

AMENDMENTS TO THE CLAIMS

1. (currently amended) A virtual disk formatting system comprising:

a ~~number~~ plurality of mass-storage devices, each having physical sectors of a first sector length; and

a routing component that provides a virtual disk interface to the mass-storage devices by ~~mapping~~ routing each access operation, received from an external entity, each access operation directed to a virtual disk having virtual sectors of a second sector length, to ~~one of~~ one or more mass-storage devices of the ~~number~~ plurality of mass-storage devices, having physical sectors of the first sector length;

wherein the first sector length and the second sector length refer to data-payload lengths of physical sectors.

2. (original) The virtual disk formatting system of claim 1 wherein the routing component is an integrated-circuit storage-shelf router.

3. (original) The virtual disk formatting system of claim 2 wherein the storage-shelf router provides a fibre-channel-disk-based virtual disk formatting interface to external entities and maps fibre-channel-disk-based access operations to a number of ATA disk drives included in a storage shelf containing the storage-shelf router.

4. (previously presented) The virtual disk formatting system of claim 1 wherein the routing component includes a processor and firmware/software programs that carry out virtual disk formatting.

5. (original) The virtual disk formatting system of claim 1 wherein virtual sectors are mapped onto contiguous physical sectors, allowing the physical sector and byte address of the first byte of a virtual sector to be calculated, when the second sector length is greater than the first sector length, as:

fsl = first sector length

ssl = second sector length

modulus = (smallest number evenly divisible by both fsl and ssl) / ssl

difference = ssl - fsl

physical sector = virtual sector + $\left(\frac{\text{virtual sector}}{\text{modulus}} \right)$

physical byte address = remainder $\left(\frac{\text{virtual sector}}{\text{modulus}} \right) \times \text{difference}$

and, when the second sector length is less than the first sector the physical sector and byte address of the first byte of a virtual sector is calculated, as:

fsl = first sector length

ssl = second sector length

modulus = (smallest number evenly divisible by both fsl and ssl) / ssl

difference = fsl - ssl

physical sector = virtual sector - $\left(\frac{\text{virtual sector}}{\text{modulus}} \right)$

physical byte address = remainder $\left(\text{fsl} - \text{remainder} \left(\frac{\text{virtual sector}}{\text{modulus}} \right) \times \text{difference} \right) / \text{fsl}$.

6. (original) The virtual disk formatting system of claim 5 wherein, when the modulus and difference are both evenly divided by 2, the division and multiplication operations can be replaced with shift operations, and the remainder operation can be replaced by a bit-wise and operation.

7. (currently amended) A virtual disk formatting system comprising:

a ~~number~~ plurality of mass-storage devices having physical sectors of a first sector length; and

a routing component that provides to external entities a first virtual disk interface to the mass-storage components by mapping each access operations, received from one of the external entities, directed to the first virtual disk interface having virtual sectors of a second sector length to an internal, virtual disk interface with internal-virtual-disk-sectors having a third sector length larger than the second sector length, and then ~~mapping~~ routing the access operations from the internal,

virtual disk interface to one or more mass-storage devices of the ~~number~~ plurality of mass-storage devices;

wherein the first sector length and the second sector length refer to data-payload lengths of physical sectors.

8. (original) A virtual disk formatting system of claim 7 further including:

including, by the routing component, error detection information within the internal-virtual-disk-interface sectors in order to provide routing-component-mediated error checking.

9. (original) The virtual disk formatting system of claim 8 wherein the error detection information is a longitudinal redundancy check code.

10. (original) The virtual disk formatting system of claim 7 wherein the routing component is an integrated-circuit storage-shelf router.

11. (original) The virtual disk formatting system of claim 10 wherein the storage-shelf router provides a fibre-channel-disk-based virtual disk formatting interface to external processing entities and maps fibre-channel-disk-based access operations to a number of ATA disk drives included in a storage shelf containing the storage-shelf router.

12. (original) The virtual routing system of claim 7 wherein the routing component includes a processor and firmware/software programs that carry out virtual disk formatting.

13. (currently amended) A method for providing a virtual-disk-format interface to processing entities external to a ~~number~~ plurality of mass storage devices, each having physical sectors of a first sector length, the method comprising:

providing a routing component; and

mapping routing each access operation, received from an external entity, each access operation directed to a virtual disk having virtual sectors of a second sector

length by the routing component to one or more of the ~~number~~ plurality of mass-storage devices having physical sectors of the first sector length;

wherein the first sector length and the second sector length refer to data-payload lengths of physical sectors.

14. (original) The method of claim 13 wherein the routing component is an integrated-circuit storage-shelf router.

15. (currently amended) The method of claim 14 wherein the storage-shelf router provides a fibre-channel-disk-based virtual disk formatting interface to external processing entities and further including:

mapping routing, by the storage-shelf router, fibre-channel-disk-based access operations to a number of ATA disk drives included in a storage shelf containing the storage-shelf router.

16. (original) The method of claim 13 wherein the routing component includes a processor and firmware/software programs that carry out virtual disk formatting.

17. (original) The method of claim 13 further including:

mapping, by the routing component, virtual sectors onto contiguous physical sectors, allowing the physical sector and byte address of the first byte of a virtual sector to be calculated, when the second sector length is greater than the first sector length, as:

fsl = first sector length

ssl = second sector length

modulus = (smallest number evenly divisible by both fsl and ssl)/ssl

difference = ssl - fsl

physical sector = virtual sector + $\left(\frac{\text{virtual sector}}{\text{modulus}} \right)$

physical byte address = remainder $\left(\frac{\text{virtual sector}}{\text{modulus}} \right) \times \text{difference}$

and, when the second sector length is less than the first sector the physical sector and byte address of the first byte of a virtual sector is calculated, as:

fsl = first sector length

ssl = second sector length

modulus = (smallest number evenly divisible by both fsl and ssl) / ssl

difference = fsl - ssl

physical sector = virtual sector - $\left(\frac{\text{virtual sector}}{\text{modulus}} \right)$

physical byte address = remainder $\left(\text{fsl} - \text{remainder} \left(\frac{\text{virtual sector}}{\text{modulus}} \right) \times \text{difference} \right) / \text{fsl}$.

18. (original) The method of claim 17 wherein, when the modulus and difference are both evenly divided by 2, the division and multiplication operations can be replaced with shift operations, and the remainder operation can be replaced by a bit-wise and operation.

19. (currently amended) A method for including additional information in disk sectors of a ~~number~~ plurality of mass-storage devices having a first sector length, the method comprising :

providing a routing component;

mapping, by the routing component, access operations, received from one of the external entities, directed to a first virtual disk interface having virtual sectors of a second sector length to an internal, virtual disk interface with internal-virtual-disk-sectors having a third sector length larger than the second sector length, and then ~~mapping~~ routing, by the routing component, the access operations from the internal, virtual disk interface to one or more of the ~~number~~ plurality of mass-storage devices;

wherein the first sector length and the second sector length refer to data-payload lengths of physical sectors.

20. (original) The method of claim 19 further including:

including, by the routing component, within the internal-virtual-disk-interface sectors one of:

- error-detection information;

- additional information that, together with the data contained in the internal-virtual-disk-interface sectors, provides an encrypted version of the data directed to the first virtual disk interface by external processing entities; and

- error-detection and error-correction information.